



F5B

Medium-Density Bare Foam Pig

<u>Size</u>	<u>Length</u>	<u>Weight</u>		<u>Size</u>	<u>Length</u>	<u>Weight</u>
2"	4"	0.17		24"	48"	70
3"	6"	0.28		26"	52"	89
4"	8"	0.68		28"	56"	118
6"	12"	2		30"	60"	125
8"	16"	4		32"	64"	155
10"	20"	8		34"	68"	185
12"	24"	11		36"	72"	214
14"	28"	19		38"	76"	249
16"	32"	22		40"	80"	291
18"	36"	32		42"	84"	337
20"	40"	41		44"	88"	390
22"	44"	56		48"	96"	511

*Weights and dimensions are approximate

Technical Description

Medium-density foam cylinder constructed of rugged open-cell foam and coated with an elastomer on the base.

Industry Applications

Primarily used for batching products and product removal; sealing behind a stuck pig with bypass; removing sludge and mud deposits; gauging pipeline conditions prior to aggressive pigging operations.



STANDARD PIG, INC.

31729 Decker Industrial Dr. · Pinehurst, TX 77362
P: 832.893.4015 · F: 281.537.2006 · E: info@standardpig.com
www.standardpig.com



F5B-DD

Medium-Density Bare Foam Pig (Double-Dish)

<u>Size</u>	<u>Length</u>	<u>Weight</u>		<u>Size</u>	<u>Length</u>	<u>Weight</u>
2"	3"	0.13		24"	36"	65
3"	5"	.26		26"	39"	83
4"	6"	.47		28"	42"	101
6"	9"	2		30"	45"	117
8"	12"	4		32"	48"	146
10"	15"	7		34"	51"	175
12"	18"	10		36"	54"	203
14"	21"	18		38"	57"	237
16"	24"	21		40"	60"	278
18"	27"	30		42"	63"	323
20"	30"	38		44"	66"	375
22"	33"	52		48"	72"	494

*Weights and dimensions are approximate

Technical Description

Medium-density foam cylinder constructed of rugged open-cell foam and coated with an elastomer on both ends.

Industry Applications

Primarily used for batching products and product removal; sealing behind a stuck pig with bypass; removing sludge and mud deposits; gauging pipeline conditions prior to aggressive pigging operations.



STANDARD PIG, INC.

31729 Decker Industrial Dr. · Pinehurst, TX 77362

P: 832.893.4015 · F: 281.537.2006 · E: info@standardpig.com

www.standardpig.com