



F5W

Medium-Density Wirebrush Foam Pig

<u>Size</u>	<u>Length</u>	<u>Weight</u>		<u>Size</u>	<u>Length</u>	<u>Weight</u>
2"	4"	0.38		24"	48"	86
3"	6"	0.67		26"	52"	104
4"	8"	1		28"	56"	122
6"	12"	3		30"	60"	140
8"	16"	6		32"	64"	173
10"	20"	10		34"	68"	206
12"	24"	16		36"	72"	240
14"	28"	24		38"	76"	279
16"	32"	28		40"	80"	325
18"	36"	41		42"	84"	376
20"	40"	54		44"	88"	433
22"	44"	70		48"	96"	563

*Weights and dimensions are approximate

Technical Description

Medium-density foam cylinder constructed of rugged open-cell foam, coated with an abrasion-resistant elastomer in a criss-cross pattern and equipped with abrasive carbon-steel wirebrush straps.

Industry Applications

Primarily used to remove rust and millscale during pipeline pre-commissioning; maintenance cleaning of pipelines; removing any type of adhered buildup on pipewalls.



STANDARD PIG, INC.

31729 Decker Industrial Dr. · Pinehurst, TX 77362
P: 832.893.4015 · F: 281.537.2006 · E: info@standardpig.com
www.standardpig.com



F5W-DD

Medium-Density Wirebrush Foam Pig (Double-Dish)

<u>Size</u>	<u>Length</u>	<u>Weight</u>		<u>Size</u>	<u>Length</u>	<u>Weight</u>
2"	3"	0.34		24"	36"	81
3"	5"	0.50		26"	39"	98
4"	6"	1		28"	42"	115
6"	9"	3		30"	45"	132
8"	12"	6		32"	48"	164
10"	15"	10		34"	51"	196
12"	18"	15		36"	54"	229
14"	21"	23		38"	57"	267
16"	24"	27		40"	60"	312
18"	27"	39		42"	63"	362
20"	30"	51		44"	66"	418
22"	33"	66		48"	72"	546

*Weights and dimensions are approximate

Technical Description

Medium-density foam cylinder constructed of rugged open-cell foam, coated with an abrasion-resistant elastomer in a criss-cross pattern and equipped with abrasive carbon-steel wirebrush straps.

Industry Applications

Primarily used to remove rust and millscale during pipeline pre-commissioning; maintenance cleaning of pipelines; removing any type of adhered buildup on pipewalls.



STANDARD PIG, INC.

31729 Decker Industrial Dr. · Pinehurst, TX 77362

P: 832.893.4015 · F: 281.537.2006 · E: info@standardpig.com

www.standardpig.com