



F8TW

Total-Wire Wirebrush Foam Pig

<u>Size</u>	<u>Length</u>	<u>Weight</u>		<u>Size</u>	<u>Length</u>	<u>Weight</u>
2"	4"	.45		24"	48"	107
3"	6"	.86		26"	52"	131
4"	8"	2		28"	56"	166
6"	12"	4		30"	60"	181
8"	16"	9		32"	64"	218
10"	20"	15		34"	68"	255
12"	24"	21		36"	72"	293
14"	28"	32		38"	76"	337
16"	32"	40		40"	80"	387
18"	36"	53		42"	84"	444
20"	40"	67		44"	88"	506
22"	44"	86		48"	96"	649

*Weights and dimensions are approximate

Technical Description

Heavy-density foam cylinder constructed of rugged open-cell foam, coated with an abrasion-resistant polyurethane elastomer and equipped with maximum coverage of abrasive carbon-steel wirebrush straps.

Industry Applications

Primarily used to aggressively remove rust and millscale during pipeline pre-commissioning; maintenance cleaning of pipelines; removing any type of adhered buildup on pipewalls.



STANDARD PIG, INC.

31729 Decker Industrial Dr. · Pinehurst, TX 77362
P: 832.893.4015 · F: 281.537.2006 · E: info@standardpig.com
www.standardpig.com